

M1901S

Specifications

19 " MultiMedia LCD Monitor

AVIDAV
Make Life Alive

LCD Panel	Type Viewing Angle Contrast Ratio Brightness Response Time Display Colors Max Resolution Pixel Pitch	19" TFT Active Matrix LCD Display H: 170", V: 170" 600:1 (Typical) 250 (Typical) 16ms 16.7M colors 1280x1024 (SXGA) 0.294mm(H)x0.294mm(V)
Input Signals	RGB Analog	Video Level:0.7Vp-p(75ohm) Sync TTL with 75ohm internal pull-up resistors Frequency FH:30~79KHz FV:56~75Hz
Compatibility	PC	Up to 1280x1024@75Hz (Non-interlaced)
Connector	RGB Analog Audio Power	D-sub 15 pins Stereo Phone Jack (L/R) 12V/DC Power Jack
Power	Voltage Consumption Power saving mode	100-240V, 50/60Hz (universal) via external AC adapter Active < 48Watt Standby < 3 Watt
Internal Speaker		2Wx2 (stereo)
User Interface	LED indicator	Active - Green Off - Turn Off Standby - Orange
Operating Condition	Temperature Air Humidity	5C~40C 20%~80% R.H.
Dimensions	Physical	463mm(H) x 436mm(W) x 64mm(D)
Net Weight		6.6Kg
DDC		DDC1/DDC2B Compliant
Power Management		VESA DPMS, EPA Energy Star
Regulation (Certifications)		CE, FCC, VCCI, BSMI, UL

