

## Mainboard Diagram



### NF91-600-LF

1. Intel 910GMLE + ICH6M Chipset
2. Support Intel ULV Celeron M 600MHz / 512K L2 cache
3. FSB 400MHz
4. Build-in Intel® GMA900 graphics
5. Solid Polymer, long life capacitors
6. Supports 1x Gigabit PCI-E LAN
7. Integrated ALC662 HD Audio CODEC with 6-CH
8. Support Jetway Expansion Daughter Boards serial
9. ITX Form Factor (17cm x 17cm)

## Board Specifications

|                    |  |
|--------------------|--|
| ■ CPU              | ■ Intel ULV Celeron M 600MHz / FSB 400MHz / 512K L2 Cache CPU  |
| ■ Chipset          | ■ Intel 910GMLE + ICH6M chipset<br>■ Built-in Intel® GMA900 Graphics   |
| ■ Memory           | ■ 1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 up to 1 GB   |
| ■ Expansion Slots  | ■ 1 * 32-bit PCI slots<br>■ 1 * PCI 120-Pin Adapter Connector With Expansion Daughter Boards   |
| ■ Storage          | ■ 2 * Serial ATA connectors<br>■ 1 * Ultra DMA 100 / 66 IDE connector  |
| ■ Audio            | ■ Realtek ALC662 6-Channel HD Audio CODEC  |
| ■ Ethernet LAN     | ■ Realtek RTL8111C PCI-E Gigabit Ethernet LAN  |
| ■ USB              | ■ Embedded 8 * USB 2.0/1.1   |
| ■ Special Features | ■ Intel Embedded Platform<br>■ Support S3 & Smart FAN features   |
| ■ Rear Panel I / O | ■ 4 * USB 2.0/1.1 ports<br>■ 1 * PS/2 Keyboard & Mouse<br>■ 1 * RJ-45 ports<br>■ 3 * Audio I / O ports ( Line-in, mic and line-out )<br>■ 1 * VGA port<br>■ 1 * DB-9 RS232 ports           |
| ■ Internal I / O   | ■ 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports<br>■ NB / Chassis Fan connectors;<br>■ 1 * 20-pin ATX Power connector<br>■ 1 * LVDS header (Support 18bits Dual Channel)<br>■ 1 * COM header |
| ■ BIOS             | ■ Award 4MB FWH Flash ROM  |
| ■ Form Factor      | ■ Mini ITX Form Factor(17cmx17cm)  |

\*For further information please visit the website at <http://www.jetwaycomputer.com/>

\*The Specification may be changed without further notice.