

HBJC150I92V

1U Rackmount Q470E Embedded Barebone Comet Lake / 1*2.5GBE+1*1GBE / 2*2.5"



Features

- 1U Rackmount Embedded Barebone
- Planned Product Lifecycle Through Q2'2035
- Supports 10th Gen Comet Lake, Socket LGA1200
- Supports DDR4 SODIMM up to 64GB Total
- 1*Intel 2.5GBE + 1*Intel 1GBE, Supports iAMT & vPro
- 2 * 2.5" or 1 * 3.5" SATA3 RAID Bays
- M.2 SATA/PCIE 3.0 x4 NVME, M.2 2230 for WIFI
- 2 * HDMI (4K), DisplayPort (4K), HD Audio
- PCIE x16 Riser Card (full-height, single slot)
- 2 * Serial, Watchdog Timer, USB 3.2 Gen2
- 250W FlexATX Power Supply

Model No.	■ JBC150I92V
Part No	■ HBJC150I92-Q470-V, HBJC150I92I-Q470-V (WIFI)
Processor	■ Supports 10 th Gen Comet Lake processors UP TO 65W, LGA1200
Memory	■ 2 * DDR4 SODIMM up to 64GB total memory
Expansion Slots	■ M.2 2230 for WIFI, 1 * PCIE x16 riser card supporting single-slot, full-height
Storage	■ 2 * 2.5" or 1 * 3.5" SATA3 bays supporting RAID 0, 1, JBOD ■ M.2 M-key SATA & PCIE 3.0 x4 NVME 2280
Network	■ 1 * Intel i225-V 2.5GBE, 1 * Intel i219-LM with iAMT, vPro
Other Features	■ ACPI S3, AHCI, Watchdog Timer 10-255 min/sec
Front Panel I/O	■ Power, Reset, LEDs, 2 * USB 2.0 ports
Rear Panel I/O	■ 2 * HDMI, DisplayPort, 4 * USB 3.2 Gen2, 2 * RJ45 LAN, 2 * Serial ports (RS232/422/485), Audio jacks, Alternative Power & Reset, 2 * Antenna Holes
BIOS	■ AMI SMT Flash ROM
Box Contents	■ US Power cord, SATA cable, Low profile CPU heatsink/fan, PCIE x16 riser card, 250W PSU
Compliance	■ CE, FCC, RoHS, ErP Ready
Temperature	■ Operating Temperature 0 - 50° C ■ Storage Temperature -10 - 70° C
Dimensions	■ 252 x 430 x 44mm (DxWxH)
Warranty	■ 2 Years limited warranty

*Specifications subject to change without notice, not responsible for typographical errors.



Jetway Computer Corporation
Phone: 510-857-0130 Fax: 510-857-0138
8058 Central Ave., Newark, CA 94560
www.jetwaycomputer.com