

# JBC152F533

## 1U POE+ Rackmount Embedded Barebone Celeron J1900 / 4GB / 8 or 16-port POE+

### Features

- Bay Trail 1U Rackmount POE+ Embedded Barebone
- Intel Celeron J1900 2.0GHz SoC Quad-Core 10W
- 4GB DDR3L-1333 Onboard Memory
- 4 \* Intel Gigabit LAN, Supports 1 \* 2.5" SATA Drive
- 8 or 16-port 10/100 LAN with POE+ (up to 30W)
- 1 \* mSATA/mini-PCIE Slot
- 2 \* Serial, VGA, USB 3.0, USB 2.0
- 400W Power Supply



<b>Model No.</b>	■ JBC152F533
<b>Part No</b>	■ HBJC152F53308-19B (8-port POE+), HBJC152F53316-19B (16-port POE+)
<b>Processor</b>	■ Intel Celeron J1900 SoC Quad-core 2.0GHz processor, 10W TDP
<b>Memory</b>	■ 4GB DDR3L-1333 onboard, non-expandable
<b>Expansion Slots</b>	■ 8-port: 1 * Full-size Mini-PCIE slot, 16-port: none
<b>Storage</b>	■ 1 * 2.5" SATA2 drive (max 9.5mm height), 1 * Full-size mSATA/Mini-PCIE slot
<b>Network</b>	■ 4 * Intel i211-AT gigabit LAN (rear) ■ 8 or 16-port 10/100 LAN with POE+ up to 30W per port, Conforms to IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at, IEEE802.3x Flow control
<b>Other Features</b>	■ ACPI S3, AHCI, Watchdog Timer 10-255 min/sec,
<b>Rear Panel I/O</b>	■ 1 * USB 3.0 port, 1 * USB 2.0 port, VGA, 4 * RJ45, 2 * Serial (1 * RS232/422/485, 1 * RS232), Antenna holes, AC Plug
<b>Front Panel I/O</b>	■ Power button, 8 or 16-ports RJ45
<b>BIOS</b>	■ AMI 64MB SMT Flash ROM
<b>Box Contents</b>	■ US Power Cord, SATA Cable, Manual, Driver disk, Mounting ears
<b>Compliance</b>	■ CE, FCC, RoHS, ErP Ready
<b>Temperature</b>	■ Operating Temperature 0~40 ° C, Storage Temperature -20-85 ° C
<b>Dimensions</b>	■ 252 x 430 x 44mm (DxWxH)
<b>Warranty</b>	■ 2 Years limited warranty

\*Specifications subject to change without notice, not responsible for typographical errors.



**Jetway Computer Corporation**  
Phone: 510-857-0130 Fax: 510-857-0138  
8058 Central Ave., Newark, CA 94560  
[www.jetwaycomputer.com](http://www.jetwaycomputer.com)