

# JBC390F541SXG

## Cableless & Fanless Embedded Barebone 2 LAN / 1 COM / 4 USB / 16bit GPIO

### Features



- Bay Trail Cableless & Fanless Embedded Barebone
- Planned Product Lifecycle Through Q1'2029
- Intel Celeron J1900 SoC Quad-Core
- Supports DDR3L-1600 SODIMM up to 8GB Total
- 2 \* Intel LAN, 1 \* COM, 4 \* USB, 16bits GPIO
- HD Audio, Up to 2 Displays, HDMI, VGA
- 1 \* 2.5" Drive Bay, 1 \* Full-size Mini-PCIE Slot (WIFI)
- 1 \* Full-size mSATA/Mini-PCIE Shared Slot
- Includes Wall Mount and Din Rail Mounting

<b>Part No</b>	<ul style="list-style-type: none"> <li>■ HBJC390F541SXG19 (no WIFI)</li> <li>■ HBJC390F541SZXG19 (with WIFI)</li> </ul>
<b>Processor</b>	■ Intel Celeron J1900 SoC Quad-core, Bay Trail
<b>Memory</b>	■ 1 * 204-pin DDR3L-1333/1600 SO-DIMM up to 8GB total memory, 1.35V required
<b>Expansion Slots</b>	■ 1 * Full-size PCI Express Mini Card slot (occupied on WIFI model)
<b>Storage</b>	■ 1 * SATA2 3Gb/s drive bay (<10mm), 1 * Full-size mSATA/Mini-PCIE shared slot
<b>Network</b>	■ 2 * Intel 211-AT gigabit LAN
<b>Other Features</b>	■ HD Audio, ACPI S3, AHCI, Watchdog Timer 10-255 min/sec,
<b>Rear Panel</b>	■ 1 * USB 3.0 port, 3 * USB 2.0 ports, HDMI, VGA, 2 * RJ45, Line-out, Microphone, Antenna holes, 1 * Serial port (RS232/422/485), +12V DC In jack, Reset
<b>Front Panel I/O</b>	■ Power button, 16bits GPIO (8in/8out), 1 * Open GEN3 bay
<b>BIOS</b>	■ AMI UEFI Flash ROM
<b>Box Contents</b>	■ 60W 12V AC Adapter, US Power Cord, Wall/DIN mount
<b>Compliance</b>	■ CE, FCC, RoHS, ErP Ready
<b>Temperature</b>	■ Operating Temperature 0~40 ° C, Storage Temperature -20-85 ° C
<b>Dimensions</b>	■ 165 x 185 x 48mm (DxWxH)
<b>Warranty</b>	■ 2 Years limited warranty

\*Specifications subject to change without notice, not responsible for typographical errors. Does not include memory, storage, optical, or OS.



**Jetway Computer Corporation**  
**Phone: 510-857-0130 Fax: 510-857-0138**  
**8058 Central Ave., Newark, CA 94560**  
**www.jetwaycomputer.com**